

# Example GTFS Feed

This example GTFS feed shows comma-delimited data samples for each file in a transit feed. The sample data files shown here aren't all related to each other. You can also [download a complete GTFS feed](#) in final form to work with as well.

## agency.txt

---

```
agency_id, agency_name, agency_url, agency_timezone, agency_phone, agency_lang
FunBus, The Fun Bus, http://www.thefunbus.org, America/Los_Angeles, (310) 555-0222, e
```

## stops.txt

---

```
stop_id, stop_name, stop_desc, stop_lat, stop_lon, stop_url, location_type, parent_stat
S1, Mission St. & Silver Ave., The stop is located at the southwest corner of the
S2, Mission St. & Cortland Ave., The stop is located 20 feet south of Mission St.,
S3, Mission St. & 24th St., The stop is located at the southwest corner of the int
S4, Mission St. & 21st St., The stop is located at the northwest corner of the int
S5, Mission St. & 18th St., The stop is located 25 feet west of 18th St., 37.761829
S6, Mission St. & 15th St., The stop is located 10 feet north of Mission St., 37.76
S7, 24th St. Mission Station, , 37.752240, -122.418450, , , S8
S8, 24th St. Mission Station, , 37.752240, -122.418450, http://www.bart.gov/stations/
```

## routes.txt

---

```
route_id, route_short_name, route_long_name, route_desc, route_type
A, 17, Mission, "The ""A"" route travels from lower Mission to Downtown.", 3
```

## trips.txt

---

```
route_id, service_id, trip_id, trip_headsign, block_id
A, WE, AWE1, Downtown, 1
A, WE, AWE2, Downtown, 2
```

## stop\_times.txt

---

```

trip_id,arrival_time,departure_time,stop_id,stop_sequence,pickup_type,drop_off_t
AWE1,0:06:10,0:06:10,S1,1,0,0
AWE1,,,S2,2,1,3
AWE1,0:06:20,0:06:30,S3,3,0,0
AWE1,,,S5,4,0,0
AWE1,0:06:45,0:06:45,S6,5,0,0
AWD1,0:06:10,0:06:10,S1,1,0,0
AWD1,,,S2,2,0,0
AWD1,0:06:20,0:06:20,S3,3,0,0
AWD1,,,S4,4,0,0
AWD1,,,S5,5,0,0
AWD1,0:06:45,0:06:45,S6,6,0,0

```

## calendar.txt

---

```

service_id,monday,tuesday,wednesday,thursday,friday,saturday,sunday,start_date,e
WE,0,0,0,0,0,1,1,20060701,20060731
WD,1,1,1,1,1,0,0,20060701,20060731

```

## calendar\_dates.txt

---

This example shows service exceptions for the Independence Day holiday in 2006. On Monday July 3, 2006, regular weekday service (service\_id=WD) is interrupted (exception\_type=2). Instead, weekend service (service\_id=WE) runs on that date (exception\_type=1). The same change applies on Tuesday July 4, as well.

```

service_id,date,exception_type
WD,20060703,2
WE,20060703,1
WD,20060704,2
WE,20060704,1

```

## fare\_attributes.txt

---

```

fare_id,price,currency_type,payment_method,transfers,transfer_duration
1,0.00,USD,0,0,0

```

```
2,0.50,USD,0,0,0
3,1.50,USD,0,0,0
4,2.00,USD,0,0,0
5,2.50,USD,0,0,0
```

## fare\_rules.txt

---

```
fare_id,route_id,origin_id,destination_id,contains_id
a,TSW,1,1,
a,TSE,1,1,
a,GRT,1,1,
a,GRJ,1,1,
a,SVJ,1,1,
a,JSV,1,1,
a,GRT,2,4,
a,GRJ,4,2,
b,GRT,3,3,
c,GRT,,6
```

## shapes.txt

---

```
shape_id,shape_pt_lat,shape_pt_lon,shape_pt_sequence,shape_dist_traveled
A_shp,37.61956,-122.48161,1,0
A_shp,37.64430,-122.41070,2,6.8310
A_shp,37.65863,-122.30839,3,15.8765
```

## frequencies.txt

---

```
trip_id,start_time,end_time,headway_secs
AWE1,05:30:00,06:30:00,300
AWE1,06:30:00,20:30:00,180
AWE1,20:30:00,28:00:00,420
```

## transfers.txt

---

```
from_stop_id,to_stop_id,transfer_type,min_transfer_time
S6,S7,2,300
S7,S6,3,
```

S23 , S7 , 1 ,

---

*Except as otherwise noted, the content of this page is licensed under the [Creative Commons Attribution 3.0 License](#), and code samples are licensed under the [Apache 2.0 License](#). For details, see our [Site Policies](#).*

*Ultimo aggiornamento: Ottobre 27, 2015.*